

Teak Cleaner 2010



High performance one step Teak cleaner.

DESCRIPTION

Teak Cleaner 2010 high performance one step cleaner concentrate in powder form.

It is exceptionally effective at cleaning and brightening teak and other natural wood. It rapidly removes dirt, oil, grime, and most stains without damaging the wood grain. It dissolves readily in ordinary tap water, is easy to apply and remove, and will not fade or alter colours of other materials accidentally contacted during application.

Teak Cleaner 2010 does not react with the joint sealer or other substrates. Use Teak Guard 2010 for cleaning and removal of your wood's surface dirt (please note, that Teak Guard 2010 may not be the product to use if there are special cleaning needs, like removal of old coatings).

RECOMMENDED FOR

Teak Cleaner 2010 is recommended for external use on old and new teak surfaces.

FEATURES & BENEFITS

- **Environmentally friendly**
- **Can be mixed in different strengths**
- **Economical**
- **Biodegradable**
- **Non corrosive to metals and painted surfaces ,**
- **Cleans off residue free**
- **Will not raise the grain**
- **Does not harm the Teak wood fibres.**

SPECIFICATIONS

Supply form	Powder
Colour	white
Density	Approx 1.10
Solvents	N/A
Flashpoint	N/A
Storage temperature	Not below 4°C /39°F
Application temperature	4 to 30 °C / 39 to 86°F

APPLICATION DIRECTIONS

Preparation and mixing :

50 ml of Teak Cleaner 2010 powder is sufficient for preparing 4 litres of cleaning solution at normal strength.

For extremely dirty surfaces and stains the concentration can be doubled to 100 ml per 4 litres. The use of warm water will maximize the cleaning ability of Teak Cleaner 2010. The warmer the water the faster and more effectively Teak Cleaner 2010 will work. Stir until thoroughly dissolved.

Teak Cleaner 2010 is most effective when used immediately after preparation. Therefore, prepare only enough solution to use in a 3 or 4-hour period.

Don't mix more than you can use up during this time.

Important. Always mix the powder into the water and not the water into the powder.

On coated Teak the cleaner should be tested first. Sanding will be required if the old coating is a lacquer or a polyurethane based product.

Oil based coatings can be removed with Teak Guard Cleaner 2010.

For preparing the teak for new coatings, and to achieve the best possible performance and appearance of the final result following procedure should be used.

Application

Pour onto the dry Teak deck and spread out with a brush or scrub pad. Allow to react for 2-3 minutes, then lightly scrub in the direction of the wood grain. Once applied, allow solution to soak for further 3- 5 minutes then lightly brush and rinse the surface with clean water. If the area being cleaned tends to dry-out during the soak period, as can happen on very hot or windy days maintain the area wet by occasionally brush over the areas. Difficult areas may benefit from longer soaking or brushing.

Repeat this process, until the entire area has been cleaned. Rinse with plenty of fresh water. Extremely dirty or grey wood may require a second application.

Teak Cleaner 2010

ESTIMATING DATA

4 litre of cleaning solution covers 20 – 30 square metre depending on the substrate conditions.
Coverage rates are a guideline only.

CLEANING

Tools should be cleaned with clean water.

STORAGE

Teak Cleaner 2010 can be stored in tightly sealed original containers for 12 months, if kept dry and at moderate temperatures.

It is important to reseal containers tightly after use. Store in a cool, dry place and protect from heat, freezing and direct sunlight. The product must be stored in accordance with national regulations.

PACKAGING

Teak Cleaner 2010 is available in 500 gram and 1 kg containers. (40 to 80 litres of cleaning solution)

PRECAUTIONS

READ ALL SAFETY DIRECTIONS AND WARNINGS ON PACKAGING BEFORE USE. REFER TO MATERIAL SAFETY DATA SHEET FOR HANDLING PROCEDURES.

Teak Cleaner 2010 is not classified as dangerous goods.

Adequate protective personal equipment should be used. Rubber gloves and safety goggles should be used. Please read the Material Safety Data Sheet.

The information, and, in particular, the recommendations relating to the application and end-use of the products, are given in good faith based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Technical information and services are freely available from the Teak-Guard Website.
Teak Guard Marine division

Sydney Office:

Ph. +61 2 9975 5602

Email info@teak-guard.com

Web site www.teak-guard.com.au